



OIL/WAXOIL APPLICATION FOR MAINTENANCE

OIL & WAX OIL FINISH: FOR USE ON ALL GEORGIAN BAY & CUSTOM OIL ORDERS

HARDWAX & OXIDATIVE MAINTENANCE OIL APPLICATION

- Using a cotton cloth or Bona terrycloth mop, pour a 1" line of maintenance oil on the floor the length of the planks and spread the oil evenly with the grain.
(The first line of oil will allow the mop cloth to absorb the oil for spreading. One more line may be needed for adequate spread of oil)
- The cloth or mop will build up with oil working across the floor providing an increase of uniform application (Be sure to spread evenly but not excessive oil throughout. If lines appear from the oil spread with the cloth mop, too much oil is being applied)
- Overlap mop strokes evenly across the floor adding each 1" line of oil as needed.
- Avoid any puddling or heavy applications. If a heavier amount of oil is desired, apply another coat of oil after each layer has dried.
- Let dry for 4 hours before walking traffic is permitted.
- Mop cloth can be thoroughly rinsed with mineral spirits/paint thinner and hung outdoors to dry for reuse. Or Immerse cloth into water for 24 hrs when complete and then dispose into the trash. Cloths can spontaneous combust when wadded up or tossed into the trash can cause smoldering smoke or result in fire without water submersion or solvent rinsing.